


GGK




Harte Greifspannbacken für SMW-AUTOBLOK Futter mit Backenschnellwechsel

- Kreuzversatz
- Für Innen- und Außenspannung

Typ	Id.-Nr.	B	H	T	G	N	S	b	L	kg / Satz	SMW-AUTOBLOK	*Spannbereich Ø		*Spannbereich Ø	
												Außen-A ₁	Innen-J ₁	Außen-A ₂	Innen-J ₂
GGK 1751	012464	25	40	16	M5	8	18	32	64	0.91	HG-F 160	25-60	132-170	40-78	150-188
GGK 1753	012466								60	0.88		50-88	105-142	68-106	122-160
GGK 1754	012467								56	0.80		75-113	79-117	93-131	97-135
GGK 2001	012469	28	45	20	M5	10	20	40	88	1.52	HG-F 210	29-56	186-240	37-94	224-280
GGK 2002	012470								66	1.28		60-117	125-182	89-155	163-220
GGK 2003	012471								66	1.19		97-153	88-145	135-191	126-183
GGK 2004	012472		40	15					87	1.39		-	54-86	-	68-124
GGK 2501	012473	40	50	22	M6	12	20	40	94	2.38	HG-F 260	35-66	192-258	64-130	256-322
GGK 2502	012474								72	2.08		70-136	122-188	134-200	186-252
GGK 2503	012475								78	2.19		100-166	92-158	164-230	156-222
GGK 2504	012476								110	2.88		-	-	-	70-134
GGK 4001	012478	50	55	25	M8	12	26	54	104	4.01	HG-F 315	60-102	200-280	88-182	280-375
GGK 4002	012479								91	3.58		124-218	84-178	204-298	164-258
GGK 4003	012480								147	5.50		-	70-160	-	-
GGK 5001	012481	60	74	35	M8	18	30	60	125	7.58	HG-F 400	60-160	240-375	145-280	350-490
GGK 5002	012482								108	6.67		150-280	120-260	265-400	240-370
GGK 5003	012483	50	56	25	M8	18	30	60	136	4.96		-	100-180	-	-

Spannbereiche




Grundbackenstellung "P"


Grundbackenstellung "O"



• SMW-AUTOBLOK
• 188



• SMW-AUTOBLOK
• 156



• SMW-AUTOBLOK
• 191