


GGK




Harte Greifspannbacken für Schunk Futter mit Backenschnellwechsel

- Kreuzversatz
- Für Innen- und Außenspannung

Typ	Id.-Nr.	B	H	T	G	N	S	b	L	kg / Satz	Schunk	Spannbereich Ø*		Spannbereich Ø*	
												Außen-A ₁	Innen-J ₁	Außen-A ₂	Innen-J ₂
GGK 1751	012464	25	40	16	M5	8	18	32	64	0.91	ROTA-S plus 160	25-50	-	-	-
GGK 1752	012465								68	0.92	ROTA THW 165	-	133-160	38-67	-
GGK 1753	012466								60	0.88	ROTA THW plus 165	-	105-134	66-95	-
GGK 1754	012467								56	0.80	ROTA-G 160	-	78-106	95-125	-
											THW 165				
											ROTA-S 160				
GGK 2001	012469	28	45	20	M5	10	20	40	88	1.52	ROTA-S plus 200	30-55	185-230	45-94	-
GGK 2002	012470								66	1.28	ROTA THW 210	60-110	130-178	100-145	165-215
GGK 2003	012471								66	1.19	ROTA THW plus 215	100-150	90-135	140-185	130-175
GGK 2004	012472		40	15					87	1.39	ROTA-G 200	-	55-84	-	70-120
											THW 210R/F				
											ROTA-S 200				
											ROTA NCWF 210				
											ROTA THWB 210				
GGK 2501	012473	40	50	22	M6	12	20	40	94	2.38	ROTA-S plus 250	35-70	200-265	65-138	265-330
GGK 2502	012474								72	2.08	ROTA-THW 250	80-145	130-195	143-205	190-260
GGK 2503	012475								78	2.19	ROTA THW plus 260	110-175	100-165	174-237	165-230
GGK 2504	012476								110	2.88	ROTA-G 250	-	-	-	80-145
											THW 250/265-R/F				
											ROTA NCW 265				
											ROTA-S 250				
											ROTA-NCWF 250				
											ROTA THWB 250				
GGK 2501	012473	40	50	22	M6	12	20	40	94	2.38	ROTA THW 315	40-92	205-280	94-179	294-370
GGK 2502	012474								72	2.08	ROTA THW plus 315	85-161	135-210	170-249	219-300
GGK 2503	012475								78	2.19	ROTA-G 315	115-190	105-180	203-278	194-270
GGK 2505	012477		43	15					98	2.49	ROTA-NCW 315	-	85-150	-	-
											ROTA- NCWF 315				
											THW 315-R				
GGK 4001 ¹	012478	50	55	25	M8	12	26	54	104	4.01	ROTA-S plus 315	50-162	230-350	118-240	305-430
GGK 4002 ¹	012479								91	3.58	ROTA THW 400	162-283	110-230	240-360	190-308
GGK 4003 ¹	012480								147	5.50	THW 400-R/F	-	100-220	-	-
											ROTA-G 400				
											ROTA-S 315				
											ROTA THWB 315				
											THW 315-F				
GGK 5001 ²	012481	60	74	35	M8	18	30	60	125	7.58	ROTA-S plus 400	80-190	260-400	170-310	380-520
GGK 5002 ²	012482								108	6.67	ROTA-S plus 500	170-310	140-280	265-405	260-400
GGK 5003 ²	012483	50	56	25	M8	18	30	60	136	4.96	ROTA THW 500	-	100-210	-	-
											ROTA-G 500				
											ROTA-S 400/500				
											THW 500-R/F				
											ROTA THWB 400				
											ROTA THWB 500				
GGK 5001	012481	60	74	35	M8	18	30	60	125	7.58	ROTA THW 630	80-230	260-445	220-430	430-640
GGK 5002	012482								108	6.67	THW 630-R	170-350	140-325	315-525	310-520
GGK 5003	012483	50	56	25	M8	18	30	60	136	4.96		-	100-250	-	-

- ¹ Spannbereich nur gültig für Futter Ø 400
² Spannbereich nur gültig für Futter Ø 500
 * Spannbereiche vorbehaltlich ohne Gewähr

Spannbereiche




Grundbackenstellung "P"


Grundbackenstellung "O"



SMW-AUTOBLOK
188



SMW-AUTOBLOK
112, 156



SMW-AUTOBLOK
191