


GSG-D




Harte Stangengreifbacken

- Spitzverzahnung Zoll 1/16" x 90° oder 3/32" x 90°
- Spitzverzahnung geschliffen

Typ	Id.-Nr.	Spann- bereich Ø	B	H	N	Spitz- verzahnung	b für ISO 4762	kg / Satz
GSG-D 165 ¹	091343	15-40	30	40	14	1/16" x 90°	20 M10	1.06
GSG-D 200 ²	091344	15-50	35	45	17	1/16" x 90°	22 M12	1.50
GSG-D 250 ³	091345	20-70	45	50	21	1/16" x 90°	28 M16	2.69
GSG-D 400 ⁴	091346	40-100	55	60	25.5	3/32" x 90°	35 M20	7.78

- * nur mit Einzelnutenstein
¹ Spannbereich gültig für Futter Ø 165
² Spannbereich gültig für Futter Ø 210
³ Spannbereich gültig für Futter Ø 260
⁴ Spannbereich gültig für Futter Ø 400

GFB-D



Harte Aufsatzbacken für GF-80

- Spitzverzahnung Zoll 1/16" x 90°
- Spitzverzahnung geschliffen

Typ	Id.-Nr.	Spann- bereich Ø	B	H	N	Spitz- verzahnung	b für ISO 4762	kg / Satz
GFB-D 1	016348	5-25	25	39	10	1/16" x 90°	M8	0.64
GFB-D 2	016349	25-45	30	39	10	1/16" x 90°	M8	0.62
GFB-D 3	016350	45-65	30	39	10	1/16" x 90°	M8	0.53
GFB-D 4	016351	65-80	30	39	10	1/16" x 90°	M8	0.47
GFB-D 5	016352	80-100	30	39	10	1/16" x 90°	M8	0.51



• SMW-AUTOBLOK
• 188, 190



• SMW-AUTOBLOK
• 65

The image consists of two solid-colored rectangular blocks. The left block is a dark blue, and the right block is a light blue. They are separated by a thin vertical white line. The dark blue block is on the left, and the light blue block is on the right.

GF 80
GF 80