


MFG



Harte Grundbacken für Backenschnellwechsel

- Modulschrägverzahnung System Forkardt
- Inklusive Backenbefestigungsschrauben ISO 4762 – 12.9

Typ	Id.-Nr.	B	H	L	N	S	G x Gewindetiefe	kg / Satz	SMW-AUTOBLOK
MFG 160	081303	20	29.5	74	18	8	M8 x 1.0 x 16	0.68	HG-F 160
MFG 200	081304	22	35	90	20	10	M8 x 1.0 x 16	1.14	HG-F 210
MFG 250	081305	26	40	110	20	12	M12 x 1.5 x 20	1.82	HG-F 260
MFG 315	081306	32	46	125	26	12	M12 x 1.5 x 25	2.90	HG-F 315
MFG 400	081307	45	55	160	30	18	M16 x 1.5 x 30	6.43	HG-F 400 HG-F 500
MFG 630	034266	65	62	230	40	24	M20 x 33	16.13	HG-F 630

Forkardt	Samchully	Kitagawa	Röhm	Schunk
F 160			Duro 160	ROTA-S 160
F+160			Duro-NC 160	ROTA-S PLUS 160
KTNC 160			Duro-NC 175	
FNC 175			Duro-NCE 160	
KTNCV 160/175				
F 200			Duro 200	ROTA-S 200
F+200			Duro-NC 200	THW 210 F
KTNC 200			Duro-NCE 200	ROTA-S PLUS 200
FNC 200			Duro-NC 225	ROTA NC-WF 210
KTNCV 200				
F 250			Duro 250	ROTA-S 250
F+250			Duro-NC 250	THW 250 F
UNC 250/315			Duro-NCE 250/315	THW 265 F
FNC 250/315				ROTA NC-WF 250
KTNC 250/280/315				ROTA NC-WF 315
KTNCV 250/315				ROTA-S PLUS 250
F 315			Duro 315	ROTA-S 315
F+315			Duro-NC 315	THW 315 F
UNC 400			Duro-NCE 400	THW 400 F
FNC 400				ROTA-S PLUS 315
KTNC 360/400				
KTNCV 400				
F 400/500-L			Duro 400/500	ROTA-S 400
F+400/500			Duro-NC 400/500	ROTA-S 500
UNC 500			Duro-NCE 500	THW 500 F
KTNC 500/630				ROTA-S PLUS 400
FNC 500/630				ROTA-S PLUS 500
KTNCV 500/630				
F 630			Duro 630	ROTA-S 630
F+630			Duro-NC 630	ROTA-S plus 630