


MHB-D



Harte, umkehrbare Aufsatzbacken für Vorderend-Kraftspannfutter


- Spitzverzahnung Zoll 1/16" x 90° bzw. 3/32" x 90°
- Spitzverzahnung geschliffen

Typ	Id.-Nr.	B	H	L	T	N	Spitzver- zahnung	a + b + c f. ISO 4762	kg / Satz	SMW- AUTOBLOK	Röhm	Schunk
MHB-D 125	013817	24	40	57.7	9	11	1/16" x 90°	9.5 + 18 + 18 M8	0.68		LV 125	TP 125-26 ROTA TP 125
MHB-D 130	12081306	29.7	34	58.1	8.5	12	1/16" x 90°	13 + 16 + 16 M10	0.60	SP 125-26 ab Bj. 98 STP 125 ab Bj. 98		
MHB-D 160	12081636	34	39	65.2	10	14	1/16" x 90°	18 + 16.5 + 16.5 M10	0.89	SP 160-38 STP 160	LVE 160	TP 160-38 ROTA TP 160
MHB-D 200	12082036	40	45	82.7	10.5	17	1/16" x 90°	19 + 23 + 23 M12	1.68	SP 200/240 STP 200/240	LVE 200	TP 200-52 ROTA TP 200
MHB-D 251	12083036	45	56	106.2	13.5	21	1/16" x 90°	26 + 30 + 30 M16	2.87	SP 250/280/350 STP 280	LVE 305 LVE 250	TP 250/315 ROTA TP 250/315 ROTA TP 350
MHB-D 315	12083186	50	56	123.6	13.5	21	1/16" x 90°	43 + 30 + 30 M16	3.72	SP 350 SP-L 350	LVE 315	TP 315 ROTA TP 315/350
MHB-D 500	12084546	60	75	140.8	19	25.5	3/32" x 90°	38 + 38 + 38 M20	7.10	BB-N 400/470 BB-N 500/600 BB-N ES 400/470 BB-N ES 500/600 BB-EXL(SC)2G 510 BB-EXL(SC)2G 660	LVE 400/500 LVE 630/800 LVE 1000	TB 400/500 ROTA EP 380/46 ROTA TB 400/500 ROTA TB 610 ROTA TB 630-265 LH
MHB-D 630 ¹	12086446	75	85	161.8	30	30	3/32" x 90°	30 + 50 + 50 M24	13.50	BB-N 630-310 BB-N ES 630 BB-AZ2G 685 BB-AZ2G 740 BB-AZ2G 1000 BB-EXL(SC)2G 900		ROTA TB 630
MHB-D 800 ¹	12088046	75	85	220	30	30	3/32" x 90°	51 + 62 + 62 M24	19.50	BB-N 800-410 BB-N ES 850 BB-N ES 1000 BB-AZ2G 685 BB-AZ2G 740 BB-AZ2G 1000 BB-EXL(SC)2G 900		TB 800/1000/1200 ROTA TB 800/850 ROTA TB 1000/1200

¹ nur 1 Spannstufe



• SMW-AUTOBLOK
• 188, 190



• SMW-AUTOBLOK
• 65