


SBJ-M


Soft pie jaws



- Metric serration 1.5 x 60°
- Material: 16MnCr5, Serration ground

Type	Id. No.	B	B ₁	H	L	D	N	Serration	a + b for ISO 4762	kg/Set	SMW-AUTOBLOK
SBJ-M 160	036016	120	50	50	60	160	12	1.5 x 60°	25 + 20 M10	5.15	HFKN-M 165 AN/AL/BH-M 165 BHM-FC 165 RC-M 165 AP/NT-M 170 BB-M 175 HB/PB/PBI-M 165
SBJ-M 200	081724	140	70	60	70	200	14	1.5 x 60°	30 + 25 M12	9.02	HFKN-M 210 AN/AL/BH-M 210 BB-M 210 BHM-FC 210 RC-M 210 AP/APL/NT-M 215 HB/PB/PBI-M 210
SBJ-M 250	081726	180	100	60	80	250	16	1.5 x 60°	30 + 30 M12	12.24	HFKN-M 260 AN/AL/BH-M 250 BB-M 250 BHM-FC 250 RC-M 250 AP/APL/NT-M 260 HB/PB/PBI-M 250
SBJ-M 315	231104	240	120	70	110	300	21	1.5 x 60°	45 + 30 M16	26.03	HFKN-M 315 BHM-FC 315 AN/AL/BH-M 315 BB-M 315 RC-M 305 AP/APL/NT-M 315 HB/PB/PBI-M 315

Howa	Samchully	Kitagawa	Schunk
HO7MA6 HO15M6 HO22M6 HO24M6 HO27M6 HO37M6 HO47M6	HC 06 HCH 06 HCL 06 HCLT 06 HCT 06 MH 206 HS 06 HSL 06 MHT 206	AS165 B-06/-106/-160-206 BB-06/-206 BL-206 • B-07 HJA 5-6 HOB-6 • HO-6 HOH-06/-106 HOH-160/-206 HOS 6 N-06/-160 • NL-06	HSL 165 ROTA NC plus185 ROTA NCF plus185 ROTA NCD 165-185 ROTA NCK 165 ROTA NCK plus 165 ROTA NC/NCF 165
HO7MA8 HO15MA8 HO23MA8	HC 08 HCH 08 HCL 08 HCLT 08 HCT 08 MH 208 HS 08 HSF 08 HSL 08 MHT 208	AS210 B-08/-108/-200/-208 BB-08/-208 BL-208 HJA 6-8 HO 8 • HOB 8 HOH-8/-108/-200 HOH-208 • HOS 8 N-08/-200 • NL-08	HSL 210 ROTA NCD 210 ROTA NCK 210 ROTA NC 210 ROTA NCF 210 ROTA NCK plus 210 ROTA NC 215 ROTA NCF plus 215
	HC 10 HCH 10 HCL 10 HCLT 10 HCT 10 MH 210 HS 10 HSF 10 HSL 10	AS250 B-10/-110/-210 B-210X/-250 BB-10/-210 BL-210 HJA 6-10/8-10 HO-10 • HOB-10 HOH-10/-110 HOH-210/-250 HOS-10 N-10/-250 • NL-10	HSL 250 ROTA NC/NCD 250 ROTA NCF 250 ROTA NCK 250 ROTA NCK plus 250 ROTA NC 260 ROTA NCF plus 260
	MH 212 HS 12 HSF 12 HSL 12	B-212 BB-212 BL-212	HSL 315 ROTA NCD 315 ROTA NCK 315 ROTA NC plus 315 ROTA NCK plus 315 ROTA NCF plus 315



SMW-AUTOBLOK
51, 62, 184, 186

SMW-AUTOBLOK
63

SMW-AUTOBLOK
74